

CONNECT CIRCLE INTERLOCK LARGE LOW BENCH



Collection: **Connect**

Designed by: **Botton + Gardiner**


CONNECT CIRCLE INTERLOCK LARGE LOW BENCH



Hardwood Blackbutt
UV-Resistant Oil



Core Powder-Coat
Black Satin



Core Powder-Coat
Charcoal Satin



Core Powder-Coat
Palladium Silver Satin



Core Powder-Coat
Matt Black Matt



Solid Powder-Coat
Coffee Satin



Solid Powder-Coat
Cove Satin



Solid Powder-Coat
Monument Matt




Solid Powder-Coat
Medium Bronze
Kinetic Flat



Textured Powder-
Coat Core Ten
Textured Metallic



Textured Powder-
Coat Asteroid
Textured Metallic




Textured Powder-
Coat Bass Textured
Metallic




Textured Powder-
Coat Textura Black




Textured Powder-
Coat Textura
Monument




Textured Powder-
Coat Textura White



Signature Powder-
Coat Deep Ocean
Satin




Signature Powder-
Coat Wedgewood
Satin



Signature Powder-
Coat Mangrove Satin



Signature Powder-
Coat Territory Red
Satin



Signature Powder-
Coat Claypot Satin



Signature Powder-
Coat Paperbark Satin



Bold Powder-Coat
Bondi Blue Gloss



Bold Powder-Coat
Leaf Satin

CONNECT CIRCLE INTERLOCK LARGE LOW BENCH



Bold Powder-Coat
Sensation Gloss



Bold Powder-Coat
Lobster Satin



Bold Powder-Coat
Moonlight Satin

CONNECT CIRCLE INTERLOCK LARGE LOW BENCH



Modern, modular, circular interlock bench seating in a large low size with Blackbutt hardwood battens and a steel frame in 27 powder-coat colours.

Description

Connect circle interlock large low modular bench seating is versatile, durable, and sustainable, making it suitable for a wide range of outdoor or indoor spaces. It connects with the Connect circle large tall bench to create a tiered seating design. These can be grouped with the range of 18 seating modules, consisting of geometric shapes, and interlocking elements that can transform any public space into a social hub.

Choose from circular or oblong seating designs with integrated urban planters and tiered heights to create simple to complex configurations. Designed in-house and made locally, Connect features certified Blackbutt hardwood battens with bullnose edging and a steel frame in 27 VOC-free powder-coat colours that can be customised to suit your project.

Made In

Australia

Dimensions

Ø2315mmW x 450mmH

Hardwood battens: 140mmW x 42mm thickness
Spacing: 5mm gap between battens

Batten Type

Class 1 + Select Grade Hardwood: Blackbutt with bullnose edging

CONNECT CIRCLE INTERLOCK LARGE LOW BENCH

Frame	Powder-coated, pre-galvanised steel
Powder Coat	<p>Core White (satin), Black (satin), Charcoal (satin), Palladium Silver (satin), Matt Black (matt), Pearl White (gloss)</p> <p>Solid Coffee (satin), Cove (satin), Monument (matt), Medium Bronze Kinetic (flat)</p> <p>Textured Core Ten (textured metallic), Asteroid (textured metallic), Bass (textured metallic), Textura Black (textured), Textura Monument (textured), Textura White (textured)</p> <p>Signature Deep Ocean (satin), Wedgewood (satin), Mangrove (satin), Territory Red (matt), Claypot (satin), Paperbark (satin)</p> <p>Bold Bondi Blue (gloss), Leaf (satin), Sensation (gloss), Lobster (satin), Moonlight (satin)</p>
Sustainability	<p>Certified Hardwood Blackbutt is locally sourced and certified by the Program for the Endorsement of Forest Certification (PEFC), the world's largest forestry certification system.</p> <p>Recycled Materials We locally source our steel. It means we know it uses recycled content and is 100% recyclable.</p> <p>Low Pollutants Our powder-coating process doesn't emit Volatile Organic Compounds (VOCs) and has Environmental Product Declarations (EPDs).</p>
Warranty	5-year warranty. View the warranty for more details.
Lead Time	6-8 weeks
Assembly & Delivery	Shipped fully assembled on pallets.
Fixing Detail	Fixed by others. Fix direct to a concrete slab or through pavers and into a concrete slab.
How to Specify	Select your batten finish Select your frame finish

CONNECT CIRCLE INTERLOCK LARGE LOW BENCH

Care Instructions

Hardwood

Cleaning

Remove any loose surface deposits with a soft bristled brush and wipe down with fresh water and a non-abrasive cloth.

Oiling

Oiling of timber will postpone natural greying, repel moisture, improve mould resistance, help maintain a smooth surface texture and enhance the grain and colour.

To maintain, lightly sand rough areas of timber and brush on one coat of timber decking oil every 6 months or as required.

Powder-Coat

Cleaning

Carefully remove any loose surface deposits with a wet sponge or soft bristled brush.

Use a soft (non-abrasive) cloth or brush and a diluted solution of mild detergent and warm water.

Ensure surfaces are thoroughly rinsed with clean fresh water after cleaning to remove all residues.

Never use thinners, abrasive cleaning agents, alcohol-based, acid or alkali cleaning agents.

Additional Comments

Hardwood is treated with a UV-resistant oil finish.

Integrated lighting and power on request.
